Fiart	39SW Technical data		
Motori	**Motorisation**	**Engines**	
2 x D4-270 DPI Volvo Penta	2 x D4-270 DPI Volvo Penta	2 x D4-270 DPI Volvo Penta	
2 x D4-300 DPI Volvo Penta	2 x D4-300 DPI Volvo Penta	2 x D4-300 DPI Volvo Penta	
2 x D4-320 DPI Volvo Penta	2 x D4-320 DPI Volvo Penta	2 x D4-320 DPI Volvo Penta	
2 x D6-400 DPI Volvo Penta	2 x D6-400 DPI Volvo Penta	2 x D6-400 DPI Volvo Penta	
2 x D6-440 DPI Volvo Penta	2 x D6-440 DPI Volvo Penta	2 x D6-440 DPI Volvo Penta	
ITA	**FRA**	**En**	**Data**
Lunghezza L_{OA}	Long L_{OA}	Length L_{OA}	12,600 m
Lunghezza L_H	Long L_H	Length L_H	11,50 m
Larghezza	Largeur	Width	3,86 m
Pescaggio	Tirant d'eau	Draft	1 m
Dislocamento	Poids	Displacement	8, 8 t
Capacità serbatoio acqua	Capacité eau douce	Water tank capacity	620 Lt
Capacità serbatoio gasolio	Capacité carburant	Fuel tank capacity	810 Lt
Serbatoio acque nere	Eaux noires	Waste tank capacity	40Lt
Categoria CE di progettazione	Categorie de classification	CE category	B
Persone imbarcabili	Capacité d'emporti	Maximum number on board	12
Posti letto	Place à dormir	Berths	2 (*)
Larghezza pozzetto	Largeur de cockpit	Cockpit beam	3,2 m
Larghezza scafo	Largeur de coque	Hull beam	3,86 m
Altezza di costruzione	Hauteur de construction	Construction height	2,44 m
Velocità	Vitesse	Speed	25-42 kn (*)
Prendisole di Prua	Bain de solei avant	Forward sundeck	2,31 m x 1,95 m
Prendisole di Poppa	Bain de solei arriére	Aft sundeck	1,75 m x 2,56 m
Dimensione pedana di poppa	Plate-forme arrière taille	Bathing platform size	1,10 m x 3,85 m
Batterie	Batteries	Batteries	6 x 145 Ah
Categoria di progettazione	Catégorie de conception	Design category	B
Portata Tender Lift	Debit planche arriére	Tender lift capacity	250 kg netti

(*) A seconda della configurazione/ En fonction de la configuration/According to the configuration.

The information contained in this document constitutes confidential material. Reproduction and dissemination, even partial, by any means and form is prohibited. They can only be used for internal use.